



**3000 Series  
15" CRT Touchmonitor**

**SPECIFICATIONS**

<b>Model</b>		1525C
<b>Case/Bezel color</b>		Beige
<b>Display type</b>		FST CRT
<b>Display size</b>		15" diagonal
<b>Display area dimensions, nominal</b>	Default	10.2" (260 mm) H x 7.7" (195 mm) V
<b>Monitor dimensions</b>	Width	14.3" (362 mm)
	Height (including base)	12.9" (328 mm)
	Depth (including base)	15.2" (385 mm)
<b>Dimensional drawing number</b>		MS500217 (available at <a href="http://www.elotouch.com">www.elotouch.com</a> )
<b>Highest recommended resolution</b>		800 x 600 at 85 Hz
<b>Resolutions presets (VESA timing)</b>		640 x 480 at 60, 72, 75, or 85 Hz; 800 x 600 at 60, 72, 75, or 85 Hz; 1024 x 768 at 60, 70, 75, or 85 Hz
<b>Dot pitch, nominal</b>		0.28 mm
<b>Video bandwidth</b>		67 MHz
<b>Scanning frequency</b>		Horizontal 30–70 kHz; vertical 50–160 Hz
<b>Input video format</b>		Analog (no proprietary video card needed)
<b>Input video signal connector</b>		Mini D-Sub 15-Pin (female)
<b>Power supply</b>		90–264 VAC, 50–60 Hz
<b>Power dissipation</b>		70 W max.
<b>Temperature</b>		Operating 0°C to 40°C; storage –40°C to 60°C
<b>Humidity</b>		Operating 10% to 90%; storage 10% to 90%; noncondensing
<b>Weight (approx.)</b>		Actual: 29 lb (13.0 kg); shipping 33 lb (15.0 kg)
<b>Warranty</b>	Monitor	2 years
	Touch technology	2 years iTouch; 5 years AccuTouch touchscreen
<b>Other features</b>		100% light transmission (iTouch) with no parallax; digital on-screen display (OSD) with lock out capability; Power Save function; rigid (removable) base; innovative touchscreen sealing; VESA DDC 1/2 B Plug and Play

**ORDERING INFORMATION**

Touch Technology	Touch Interface	Surface Treatment	Elo Part Number	Agency Approvals
iTouch	Serial	Antireflective	396036-000	UL, cUL, FCC, CE, CISPR22 Class B, TÜV-GS, MPR II (ITE per IEC/EN 60950)
iTouch	USB	Antireflective	634572-000	UL, cUL, FCC, CE, CISPR22 Class B, TÜV-GS, MPR II (ITE per IEC/EN 60950)
AccuTouch	Serial	Antiglare	748998-000	UL, cUL, FCC, CE, CISPR22 Class B, TÜV-GS, MPR II (ITE per IEC/EN 60950)
AccuTouch	USB	Antiglare	630062-000	UL, cUL, FCC, CE, CISPR22 Class B, TÜV-GS, MPR II (ITE per IEC/EN 60950)

- Users should independently evaluate the suitability of the product for their application.
- All prices, models, and availability subject to change without notice.

- Stock quantities may be limited. Larger quantities are available within one week.
- For Product Agency Certifications refer to our Web site.