

**1725C/1726C**

**Desktop**

**3000 Series  
17" CRT Touchmonitors**



**SPECIFICATIONS**

<b>Model</b>	1725C/1726C	
<b>Case/Bezel color</b>	Beige/dark gray	
<b>Display type</b>	FST CRT	
<b>Display size</b>	17" diagonal	
<b>Display area dimensions, nominal</b>	Default	11.8" (300 mm) H x 8.9" (225 mm) V
<b>Monitor dimensions</b>	Width	15.9" (404 mm)
	Height (including base)	14.2" (360 mm)
	Depth (including base)	16.8" (426 mm)
<b>Dimensional drawing number</b>	MS500218 (available at <a href="http://www.elotouch.com">www.elotouch.com</a> )	
<b>Highest recommended resolution</b>	1024 x 768 at 85 Hz	
<b>Resolution presets</b>	640 x 480 at 60, 72, 75, or 85 Hz; 800 x 600 at 60, 72, 75, or 85 Hz; 1024 x 768 at 60, 70, 75, or 85 Hz; 1152 x 864 at 75 Hz; 1280 x 1024 at 60 Hz	
<b>Dot pitch, nominal</b>	0.27 mm	
<b>Video bandwidth</b>	67 MHz	
<b>Scanning frequency</b>	Horizontal 30–70 kHz; vertical 50–160 Hz	
<b>Input video format/connector</b>	Analog (no proprietary video card needed)	
<b>Input power connector</b>	Mini D-Sub 15-Pin (female)	
<b>Power supply</b>	90–264 VAC, 50–60 Hz	
<b>Power dissipation</b>	75 W max.	
<b>Temperature</b>	Operating 0°C to 40°C; storage –40°C to 60°C	
<b>Humidity</b>	Operating 10% to 90%; storage 10% to 90%; noncondensing	
<b>Weight (approx.)</b>	Actual 32 lb (14.5 kg); shipping 37 lb (17.0 kg)	
<b>Warranty</b>	Monitor	2 years
	Touch technology	2 years iTouch; 5 years AccuTouch touchscreen
<b>Other features</b>	100% light transmission (iTouch) with no parallax; digital on-screen display (OSD) with lock out capability; Power Save function; rigid (removable) base; innovative touchscreen sealing; VESA DDC 1/2 B Plug and Play	

**ORDERING INFORMATION**

	<b>Touch Technology</b>	<b>Touch Interface</b>	<b>Surface Treatment</b>	<b>Elo Part Number</b>	<b>Agency Approvals</b>
Beige	iTouch	Serial	Antireflective	045182-000	UL, cUL, FCC, CE, TÜV-GS, MPR II
Beige	iTouch	USB	Antireflective	454000-000	UL, cUL, FCC, CE, TÜV-GS, MPR II
Beige	AccuTouch	Serial	Antiglare	872230-000	UL, cUL, FCC, CE, TÜV-GS, MPR II
Beige	AccuTouch	USB	Antiglare	421496-000	UL, cUL, FCC, CE, TÜV-GS, MPR II
Dark gray	iTouch	Serial	Antireflective	D95678-000	UL, cUL, FCC, CE, TÜV-GS, MPR II
Dark gray	iTouch	USB	Antireflective	D90404-000	UL, cUL, FCC, CE, TÜV-GS, MPR II
Dark gray	AccuTouch	Serial	Antiglare	C25599-000	UL, cUL, FCC, CE, TÜV-GS, MPR II
Dark gray	AccuTouch	USB	Antiglare	816802-000	UL, cUL, FCC, CE, TÜV-GS, MPR II

- Users should independently evaluate the suitability of the product for their application.
- All prices, models, and availability subject to change without notice.

- Stock quantities may be limited. Larger quantities are available within one week.
- For Product Agency Certifications refer to our Web site.